

RAVELLI S.p.A.

Via Kupfer, 31 25036 Palazzolo sull'Oglio (BS) Tel. + 39 030 7402939 Fax +39 030 7301758

DECLARATION OF PERFORMANCE

Declaration of performance according to Regulation (EU) 305/2011

n. 088CPR13.07

1. Unique identification code of the product type:

039-00-001A, residential space heating appliance with water fired by wood pellets

EN 14785:2006

- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11(4): HRV 100 TOUCH
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Residential space heating appliance with water fired by wood pellets

Name, registered trade name or registered trade mark and contact address of the manufacturer as required by Art. 11 (5):

Ravelli S.p.A.

Via A. Kupfer, 31

25036 Palazzolo s/O (Bs) Italia

- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2);
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
- In case of the declaration of performance concerning a construction product covered by a harmonised standard;
 The notified laboratory TUV RheinlandEnergie GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K18792016T1

Declared performance

Harmonizedtechnicalspecification:	EN 14785:2006				
Essentialcharacteristics	Performance				
Firesafety					
Reaction to fire	Al				
Distance to combustiblematerials	Minimum distances (mm): rear = 100 sides = 150 front = 800 ceiling = floor =				
Risk of burning fuel falling out	Pass				
Emission of combustion products (at 13% of O ₂)	Nominal heat output CO 0,010 % NOx 130 mg/Nm³ OGC 2 mg/Nm³ PM 13 mg/Nm³ Reduced heat output CO 0,048 % OGC 12 mg/Nm³				
Surface temperature	Pass				
Electricalsafety	Pass				
Cleanability	Pass				
Maximum operating pressure	2 bar				
Flue gas temperature at nominal heat output	124,5°C				
Mechanical resistance(to carry a chimney/flue)	NPD				
Nominal heat output	12,1 kW				
Room heating output	2,0 kW				
Water heating output	10,1 kW				
Efficiency	Π 91,2 % Nominal heat output Π 91,1 % Reduced heat output				

9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance
	is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer		Giovanni Scarlini, CEO	(pame and title)
Place Palazzolo s/O	Date	1-9-2016	Sign